

AHTS "MED SILVER"



GENERAL

YARD DELIVERY DATE BASIC FUNCTIONS

CLASSIFICATION

FLAG OWNER

DIMENSION

LENGTH O.A. BEAM MLD. DEPTH MLD. DRAFT MAX DEADWEIGHT APPROX DECK CARGO MAX DECK AREA APPROX OFFSHORE SUPPLY, TOWING, ANCHOR HANDLING OPERATIONS, FIRE FIGHTING AND OIL RECOVERY OPERATIONS ABS A1, TOWING VESSEL, AH, FIRE FIGHTING VESSEL CLASS 1, OFFSHORE SUPPORT VESSEL, (E), AMS, ACCU, DPS-2 NOBLE DENTON APPROVED ITALIAN MED OFFSHORE S.P.A. – ITALY

JIANGSU ZHENJIANG, CHINA

70.70 M 16.00 M 7.20 M 6.20 M 2246 TONS 800 TONS 450 M²

850 м³

655 м³

670 м³

280 м³

490 м³

490 м³

2009

TANK CAPACITIES

FUEL OIL (SHIP+CARGO) FRESH WATER BALLAST/DRILL WATER CEMENT TANK (4 TANKS) LIQUID MUD/BRINE/BASE OIL RECOIL, P.I. >60° C

(IN VARIOUS CARGO CONFIGURATIONS)

PERFORMANCES

SPEED BOLLARD PULL 14 кN 132.8 толз

PROPULSION SYSTEM

MAIN ENGINES 2 x Mak, EACH 5440 BHP PROPELLER 2 x CPP, IN NOZZLES, BERG PROPULSION BOW THRUSTER 2 x 800 BHP, 9.5T EACH KAWASAKI CPP STERN THRUSTER 2 x 800 BHP, 9.5 T EACH KAWASAKI CPP AUXILIARY EQUIPMENT 2 x 2000 KW SHAFT DRIVEN

2 x 580 KW CATERPILLAR 3412 1 x EMERGENCY GENERATOR SET 95 KW CATERPILLAR

DETAILS BELIEVED TO BE CORRECT, BUT NOT GUARANTEED

FIRE FIGHTING SYSTEM

CLASS 1 WITH WATER CURTAIN ALL AROUND FIREPUMP 2 x 1500 M3/H MONITORS 2 x 1200 M3/H

DYNAMIC POSITIONING

DP-2 DYNAMIC POSITIONING SYSTEM KONGSBERG K-POS DP2

DECK EQUIPMENT

ANCHOR WINDLASS 13 T @ 11 M/MIN GYPSIES 2 X 76 MM BOW ANCHORS 2 X 2100 KG CHAINS 2 X 440 M (L) X 42 MM (DIA) CAPSTAN 2 X 10 MT TUGGER WINCH 2 X 10 MT 0-30 M/MIN DECK CRANE 1 X 5 T @ 17 M RADIUS 1 X BRATTVAAG LOW PRESSURE HYDRAULICALLY DRIVEN DOUBLE DRUMS ANCHOR HANDLING/TOWING WINCH UPPER DRUM CAP (TOW) 2000 M (L) \times 76 MM (DIA) SWR LOWER DRUM CAP (AH) 2000 M (L) X 76 MM (DIA) SWR STALL PULL 300 M @ 1st LAYER BRAKE CAPACITY 450 MT STATIC @ 1st LAYER, REMOTE CONTROL FROM AFT CONTROL STAND IN WHEELHOUSE MAIN TOWING WIRE: 1.000 M - DIAM 71 MM SPARE TOWING WIRE: 1.000 M - DIAM 71 MM A.H. WIRE: 500 M - DIAM 58 MM STERN ROLLER 6.0 M (L) X 2.5 M (DIA) PLIMSOLL; SWL 450 MT SHARK JAWS 2 X KAMOY, SWL 300 T: TOW PINS 2 X SWL 300 T ROPE REEL 2 X PENNANT WIRE REELS, 6.7 M PULL DRUM CAPACITY 2000 M (L) X 76 MM (DIA) SWR 1 X SOLAS APPROVED RESCUE BOAT WITH DAVIT SYSTEM 1 X WORK BOAT 7.20 M

CARGO HANDLING SYSTEM

FUEL OIL 2 X 150 M3/H @ 80 M HEAD FRESH WATER 1 X 150 M3/H @ 80 M HEAD LIQUID MUD 2 X 100 M3/H @ 50 M HEAD BULK CEMENT 2 X 40 M3/H @ 5 BAR

ACCOMODATION

32 BERTHS (CREW INCLUDED) ALL CABINS FULLY AIR CONDITIONED & ALL C/W ATTACHED TOILET

NAUTICAL AND COMMUNICATION EQUIPMENT

RADIO EQUIPMENT GMDSS AREA A-3 NAUTICAL EQUIPMENT COMPRISES: 1 x X- and S- band radar system, 1 auto-pilot, 3 x gyro-compass, 2 x dgps, 1 x echo sounder, 1 x speed log, 1 x v-sat, 1 x tv-sat others as per solas regulations